

Six Powerful Models

Table of Contents - Color Coded Sections

	WV-1/4™	2" - 4" Lines for Cart & Trailer Jetters	Pages 3 - 4
	WT-3/8™	3" - 6" Lines for Cart & Trailer Jetters	Pages 5 - 6
	WS-1/2™	4"-8" Lines for Trailer Jetters & Accessories	Pages 7 - 9 Page 10
	WH-1/2™ WH-3/4™	Two WH™ Models for 6" - 18" Lines	Pages 11 - 13
	WG-1™ WD 1-1/4™	8" - 36" Lines for Municipal Jetters	Pages 14 - 17

The WARTHOG® Family of Sewer Nozzles

- **Controlled Rotation Cleans Better**

With our patented engineering, jets clean pipes more effectively at a controlled and more productive speed.

- **Fewer Jets Deliver More Power**

You get more power per jet resulting in superior root cutting and unmatched wall cleaning.

- **Easy Field Maintenance**

Customers spend an average of only 15 minutes per year replacing the seals. Step by step instructions make it simple.

- **Replaceable Nozzle Tips**

Hard hitting **StoneAge®** Attack Tip™ nozzles are field replaceable and keep your tool performing at its best.

All these features make it possible to cut roots, clear grease, ice blockages and remove hard mineral deposits with just one tool!

WARTHOG® - 6 Models to Fit Your Pumps

MODEL	PIPES	PRES.	FLOW	LENGTH	DIAM.	INLET PORT
WV-1/4™	2" - 4"	4k psi	3-8 gpm 11-30 lpm	2.0 in	1.3 in.	1/4" npt & BSPP
WT-3/8™	3" - 6"	4k psi	5-12 gpm 20-45 lpm	3.0 in.	1.9 in.	3/8" npt & BSPP
WS-1/2™	4" - 8"	4k psi	8-20 gpm 25-75 lpm	4.4 in.	1.7 in.	1/2" npt
WH-1/2™ & 3/4™	6" - 18"	8k psi	10-45 gpm 40-170 lpm	7.5 in.	3.1 in.	1/2" or 3/4" npt or BSPP
WG-1™	8" - 36"	3k psi	50-80 gpm 190-300 lpm	9.1 in.	4.2 in.	1" npt or BSPP
WD 1-1/4™	8" - 36"	3k psi	80-120 gpm 300-450 lpm	9.1 in.	4.2 in.	1-1/4" npt or BSPP